

CLAIMS

1. (previously amended) A chip rate base band processor which receives digital information containing symbol information and provides a symbol output, comprising:
- an input memory which stores the digital information;
 - a data PN code buffer;
 - a pilot PN code buffer;
 - a pilot multiplier having a first input coupled to the pilot PN code buffer, a second input coupled to the input memory, and an output;
 - a data multiplier having a first input coupled to the data PN code buffer, a second input coupled to the input memory, and an output;
 - a pilot correlator having an input coupled to the output of the first multiplier, and an output;
 - a pilot memory coupled to the pilot correlator;
 - a channel estimator coupled to the pilot memory;
 - a peak detector coupled to the pilot memory;
 - a data correlator coupled to the data multiplier;
 - load controller having a first input coupled to the peak detector, a second input coupled to data correlator, and an output;
 - a data memory coupled to the load controller;
 - a phase rotator having a first input coupled to the channel estimator, a second input coupled to the data memory, and an output; and
 - a symbol combiner having an input coupled to the phase rotator, and an output which provides the symbol output.
2. (original) The chip rate base band processor of claim 1 further comprising a cluster tracker having an input coupled to the pilot memory, and an output coupled to the pilot PN code buffer.
3. (original) The chip rate base band processor of claim 1 wherein the output of the cluster tracker is coupled to the data PN code buffer.

4-6. (cancelled).

7. (currently amended) In a chip rate base band receiver processor which receives digital information containing symbol information, wherein each symbol of the symbol information is of a predetermined time duration, a method comprising the steps of:

storing a first scan window of the digital information;

scanning the first scan window for all instances of a first symbol of the symbol information;

~~multiplied a PN code with a first segment, corresponding to a first multi-path and representative of the predetermined time duration, of the stored digital information and~~

storing a second scan window of the digital information; and

scanning the second scan window for all instances of a second symbol of the symbol information

~~multiplied the PN code with a second segment, corresponding to a second multi-path and representative of the predetermined time duration, of the stored digital information.~~

8. (cancelled)

9. (currently amended) The method of claim 7, wherein scanning the first scan window is achieved by a first PN code and scanning the second scan window is achieved with a second PN code.

10-17. (cancelled)

18. (new claim) The method of claim 7, wherein the second symbol immediately follows the first symbol in the symbol information.

AUG.14.2003 9:10AM

CORPLAW 512 996 6853

NO.585 P.5

Blk.
19. (new claim) The method of claim 7, wherein the second scan window overlaps the first scan window.
